



## **RayCat 65124 Technical Bulletin** Cationic Acrylic Dispersion

RayCat 65124 is a cationic, self-crosslinking, water-resistant acrylic latex designed for use in construction, textile and adhesive industries. Coatings formulated with RayCat 65124 will exhibit excellent water resistance and have tough and flexible films.

### **Key Features**

- Tough and flexible film
- Excellent water resistance
- Wash durable

### **RayCat 65124 Typical Physical Properties\***

Polymer type	Acrylic emulsion polymer
Weight solids	31%
Viscosity (Brookfield Model RVT)	150 cps, #3/100 rpm
pH	3.5
Tg (Calculated)	-5°C
MFFT (ASTM D-2354)	<0°C
Particle size (Mean)	0.15 microns
Surfactant charge	Cationic
Weight per gallon	8.80 lbs/gal
Freeze thaw stability	Do Not Freeze

*\* These properties are typical, but do not constitute specifications*

---

For more than 45 years, Specialty Polymers has been developing state of the art resins for the paint, coatings and adhesive industries. With more than 300 products to choose from, Specialty Polymers has the right polymer to meet your needs.

#### **IMPORTANT INFORMATION**

If any product is defective in workmanship or materials, Specialty Polymers, Inc. will replace the product. The information contained in this Technical Bulletin is intended to be a guideline. It is offered in good faith, but without guarantee. We recommend users of the product perform their own testing to determine the suitability of the product in their application.