



## RayCryl 1526 Technical Bulletin

### 100% Acrylic Emulsion

RayCryl 1526 is an APEO-free, 100% acrylic emulsion polymer designed for both interior and exterior trim enamel applications. It exhibits high gloss, good color acceptance and excellent rheology response. RayCryl 1526 provides excellent adhesion to wood, aged alkyds, and cementaceous substrates. It imparts very good water resistance for low VOC concrete sealers.

#### Key Features

- Excellent gloss and adhesion
- Outstanding rheology response
- Good water resistance

#### RayCryl 1526 Typical Physical Properties\*

Polymer type	100% Acrylic emulsion polymer
Weight solids	50%
Viscosity (Brookfield Model RVT)	110 cps, #2/100 rpm
pH	8.5
MFFT (ASTM D-2354)	9°C
Tg (MDSC)	25°C
Particle size (Mean)	0.20 microns
Surfactant charge	Anionic
Weight per gallon	8.6 lbs/gal
Freeze thaw stability	Passes

*\* These properties are typical, but do not constitute specifications.*

---

For more than 45 years, Specialty Polymers has been developing state of the art resins for the paint, coatings and adhesive industries. With more than 300 products to choose from, Specialty Polymers has the right polymer to meet your needs.

#### IMPORTANT INFORMATION

If any product is defective in workmanship or materials, Specialty Polymers, Inc. will replace the product. The information contained in this Technical Bulletin is intended to be a guideline. It is offered in good faith, but without guarantee. We recommend users of the product perform their own testing to determine the suitability of the product in their application.