



RayCryl 4124 is an acrylic, self-crosslinking acrylic designed for concrete and wood applications. It has good hot wet block resistance as a concrete sealer and excellent chemical and scratch resistance.

Key Features

- Passes KCMA testing
- Excellent water and chemical resistance
- Outstanding adhesion to multiple substrates
- High gloss

RayCryl 4124 Typical Physical Properties*

Polymer type	Acrylic emulsion polymer
Weight solids	47%
Viscosity (Brookfield Model RVT)	525 cps, #3/100 rpm
pH	7.0
Tg (MDSC)	64°C
MFFT (ASTM D-2354)	69°C
Particle size (Mean)	0.09 microns
Surfactant charge	Anionic
Weight per gallon	8.8 lbs/gal
Freeze thaw stability	Do Not Freeze
Recommended solvent loading	20-25% on solids PnB, Texanol, DPnB, PnP, Propylene Glycol

** These properties are typical, but do not constitute specifications.*

For more than 45 years, Specialty Polymers has been developing state of the art resins for the paint and coatings industry. With more than 300 products to choose from, Specialty Polymers has the right polymer to meet your needs.

IMPORTANT INFORMATION

If any product is defective in workmanship or materials, Specialty Polymers, Inc. will replace the product. The information contained in this Technical Bulletin is intended to be a guideline. It is offered in good faith, but without guarantee. We recommend users of the product perform their own testing to determine the suitability of the product in their application.