



RayRez 122 Technical Bulletin

Styrene Acrylic Emulsion

RayRez 122 is a styrene acrylic emulsion polymer that has high gloss and good adhesion. It is ideal for use in flexographic and rotogravure inks and coatings. Inks or coatings formulated from RayRez 122 have fast dry, great rub resistance and excellent transfer for paper and paperboard applications.

Key Features

- High gloss and outstanding rub resistance
- Good adhesion and ink transfer properties
- Fast dry

RayRez 122 Typical Physical Properties*

Polymer type	Styrene acrylic emulsion polymer
Weight solids	46.5 – 48.5%
Viscosity (Brookfield Model RVT)	1300 – 2400 cps, #3/100 rpm
pH	9.0 – 9.5
Tg (Calculated)	8°C
MFFT (ASTM D-2354)	0°C
Particle size (Mean)	0.07 – 0.09 microns
Weight per gallon	8.72 lbs/gal
Freeze thaw stability	Do Not Freeze

** These properties are typical, but do not constitute specifications*

For more than 45 years, Specialty Polymers has been developing state of the art resins for the paint, coatings and adhesive industries. With more than 300 products to choose from, Specialty Polymers has the right polymer to meet your needs.

IMPORTANT INFORMATION

If any product is defective in workmanship or materials, Specialty Polymers, Inc. will replace the product. The information contained in this Technical Bulletin is intended to be a guideline. It is offered in good faith, but without guarantee. We recommend users of the product perform their own testing to determine the suitability of the product in their application.