



RayVace 674 Technical Bulletin

All-Purpose Vinyl Acrylic

RayVace 674 is an all-purpose vinyl acrylic for interior paints and coatings. It has excellent scrub resistance and color acceptance and can be used in a wide variety of applications.

Key Features

- Easy to formulate
- High scrub resistance
- Excellent color acceptance
- High performance and excellent value
- Can be formulated to ultra-low VOC levels

RayVace 674 Typical Physical Properties*

Polymer type	Vinyl acrylic emulsion polymer
Weight solids	55%
Viscosity (Brookfield Model RVT)	400 cps, #3/100 rpm
pH	4.6
Tg (MDSC)	22°C
MFFT (ASTM D-2354)	7°C
Particle size (Mean)	0.39 microns
Surfactant charge	Nonionic/anionic
Weight per gallon	8.9 lbs/gal
Freeze thaw stability	Do Not Freeze

** These properties are typical, but do not constitute specifications*

For more than 45 years, Specialty Polymers has been developing state of the art resins for the paint, coatings and adhesive industries. With more than 300 products to choose from, Specialty Polymers has the right polymer to meet your needs.

IMPORTANT INFORMATION

If any product is defective in workmanship or materials, Specialty Polymers, Inc. will replace the product. The information contained in this Technical Bulletin is intended to be a guideline. It is offered in good faith, but without guarantee. We recommend users of the product perform their own testing to determine the suitability of the product in their application.